



MC-10/100/100CU-SFP-SO

Tech Specs

MC-10/100/100CU-SFP-SO

10/100/1000 Media Converter RJ-45 to SFP card, to be used in MC-16SLOT-CH-AC-SO, Jumbo MTU support, Solid Optics

1. PRODUCT INTRODUCTION

10/100M, 10/100/1000M remote manageable fiber media converters offer a high price/performance ratio; cover all functions of non-manageable fiber media converter including variety of data rate, SM/MM, single fiber and double fiber etc. with simple set-up and complete function management interface, it supports protocols like SNMP, WEB, TELNET and CONSOLE, and realizes the integrated management to all chassis.

2. PRODUCT SPECIFICATION & FEATURES

- Support 10Base-T, 100Base-TX, 1000Base-T.
- Meet standards IEEE802.3z, IEEE802.3u, IEEE802.3x and IEEE802.3ah.
- With high performance auto-sensing exchanging chipset meeting industrial standard, securing steady and non-traffic jam data transmission and exchanging.
- Max. 9K bytes packet at store-and-forward mode, Max.
- AUTO-MDIX at electrical port, convenient for the user.
- Low power consumption, low heat, standalone type with 10W special communication power supply, chassis with dual redundant power supply.
- Max safety power 100W to ensure the stable work of the equipments.
- Hot swap media converter (in card type) and management card single fiber or double fiber (single fiber media converters should be used in pair), standalone type or 16 slots chassis are optional 3R Repeater

3. ADVANTAGES

- Master-and-slave structure, Max. cascading chassis number is 4.
- The failure of the management card won't influence the work of other modules.
- Supporting remote and local management.
- Supporting protocols like CONSOLE, WEB and SNMP.
- Interface for management: RS232 Console Port (RJ45) and 10/100Mbps RJ-45 Ethernet port.
- Complete system information can be set up and displayed, including the name of the chassis, terrain information, IP address and the versions of the hardware and software.
- The status of 10/100M media converters with IPI13A/C/F/M chipsets can be monitored and queried at the same chassis system.
- 10/100/1000M media converter card support SFP, CWDM SFP, DWDM SFP and can also display its DDM function.
- Media converter card supports protocols like Q-in-Q Double Tag VLAN, IEEE802.1q Tag VLAN and IEEE802.3x Flow control.
- Detailed information regarding power supply can be tracked including AC or DC, power and present working status.
- Real time display of voltage and temperature on the cards of the media converters.
- Each port at local or remote devices can be set up or tracked, including the connecting status, connecting speed, half/full duplex, port locked and LFP.
- With rate limiting, any rate between 0Mbps and 100M bps can be set at the basic frame of 32Kbps, and any rate between 0Mbps and 1000M bps can be set at the basic frame of 64Kbps.
- Supporting Link Loopback test, precisely locating the failure, convenient for link test.
- Remote power off alarming, precisely distinguish remote failure.
- With SNMP protocol, Trap Destination and Community Name and related right can be set up, real time receive and display of alarming information in way of SNMP Trap, special supervising window, bumping alarming information.
- Offering MIB files, convenient to be merged to the third party's software like Openview and SNMPC.
- Powerful historical alarming and operating log information tracking and management function.
- Flow statistic and pre-alarming function, real-time display of the communication status at each port.
- Support Equipment remote-restart, system or module restart by management software.
- With graded management mode (common user, super user and administrator), and user identification function.
- Reset to factory set up or dip switch status are optional.
- Supporting online upgrading by FTP.
- NMS supports network device auto-detect and auto-adding.
- Real-time display of voltage and temperature on the chassis and the operating status of the fans.
- With centralized management and Top tree, several chassis can be managed in the same interface at the same time; with grouping management any converter can be conveniently manipulated among many converters

4.ORDER INFORMATION

Model No	Description
MC-10/100/100CU-SFP-SO	Card, to be used in conjunction with chassis (MC-16SLOT-CH-AC-SO)
MC-10/100/100CU-SFPS-SO	Kit card (MC-10/100/100CU-SFP-SO) + 1 slot AC chassis

5. GENERAL SPECIFICATION

Items	Technical Indexes	
Ethernet Interface	Meet Standards	IEEE802.3z, IEEE802.3u, IEEE802.3x and IEEE802.3ah
	Date Rate	10Mbps, 100Mbps, 1000M half/full duplex auto-sensing
	Connector	RJ-45
	-	UTP CAT5 or CAT5E connecting with RJ-45, transmission distance at 100m.
Fiber port	Connector	ST, SC, FC
	Operating Wavelegth	850nm, 1310nm at Multi-mode; 1310nm, 1550nm at single mode.
	Optical Fibers	Multi-mode: 50/125 62.5/125 100/140um;
	Single Mode	8.3/125,8.7/125,9/125,10/125um
Work Enviroment	Operating Temp	0°C~50°C
	Storage Temp	-10°C~70°C
	Humidity	5%~90% (non-condensing)
	Power Supply	85VAC~265VAC or -40VDC~-57VDC

5. WARNING & SYMBOLS



Solid Optics EU N.V. has tested the equipment based on European legislation. It is safe to use, doesn't intervene with other electronic devices and it is not affected by interference from other Electronic devices



Hazardous Goods; Our equipment complies with Directive 2011/65/EU (RoHS II) and 2002/95 EC (RoHS I).



Only (dis)connect the equipment in a EPA (ESD Protected Area) while using only certified equipment and taking all necessary precautions.

6. DISCLAIMER & COPYRIGHT

This document is written with the utmost care. Specifications, figures, data and illustrations provided in this document are based on information that is believed to be reliable and accurate. We don't accept any liability for damages derived from incomplete, inaccurate, outdated and/or otherwise incorrect specifications, figures, data or illustrations. We do not intend to suggest that we are the creators or trademark owners of any other manufacturers' products. Information is subject to change without notice. Solid Optics and the Solid Optics logo are registered trademarks of Solid Optics EU Holding N.V. All other trademarks are acknowledged as registered trademarks and proprietary to their respective owners. Copyright © 2019 Solid Optics EU N.V., Dutch Chamber of Commerce no. 39099087, all rights reserved. For more information visit www.solid-optics.com



Get in touch



EU Customer Support
+31 (0) 88 342 3776
info@solid-optics.com



US Customer Support
+1 855 678 4271
infous@solid-optics.com